



PARTS LIST

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B
2.	COVER	CAST IRON, ASTM A126-B
3.	SEAT	BUNA-N & 304 STAINLESS STEEL
4.	COVER BOLTS	STEEL, ASTM A307
5.	FLOAT BALL	316 STAINLESS STEEL
6.	PIPE PLUG	STEEL
7.	CUSHION	BUNA-N
8.	COVER NUTS	STEEL, ASTM A307
9.	COWL	STEEL
10.	COWL BOLTS	STEEL, ASTM A307
11.	COWL WASHER	STEEL
12.	FLOAT GUIDE	316 STAINLESS STEEL
13.	GUIDE BEARING	SELF LUBRICATING POLYMER

FIGURE NUMBER	FLANGE CLASS	WORKING PRESSURE	HYDRO TEST PRESSURE
930-DC	ANSI B16.1 CLASS 125	10-150 PSI (69-1034 kPa)	225 PSI (2068 kPa)
930-UT	ANSI B16.1 CLASS 250	10-300 PSI (69-1551 kPa)	450 PSI (3102 kPa)

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

SIZE	INLET	A	B	WGT
6" (DN150)	6" FLANGE	15.25" (387mm)	20.75" (527mm)	175 lbs (80 kg)
8" (DN200)	8" FLANGE	19.00" (483mm)	25.25" (641mm)	335 lbs. (152 kg)

GA INDUSTRIES, a VAG Brand		
DATE:	5-27-19	DRAWN BY: WJN
6" & 8" KINETIC AIR & VACUUM VALVE		
FIGURE 930	DRAWING NO. EAV-7049-W	REV A