



PARTS LIST		
ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B
2.	COVER	CAST IRON, ASTM A126-B
3.	SEAT	BUNA-N RUBBER
4.	FOLLOWER RING	316 STAINLESS STEEL
5.	SEAT SCREWS	18-8 STAINLESS STEEL
6.	O-RING	BUNA-N RUBBER
7.	COVER BOLTS	STEEL, ASTM A307
8.	CUSHION	BUNA-N RUBBER
9.	FLOAT GUIDE	316 STAINLESS STEEL
10.	FLOAT BALL	316 STAINLESS STEEL
11.	PIPE PLUG	MALLEABLE IRON
12.	COWL	STEEL
13.	COVER NUTS	STEEL, ASTM A307
14.	COWL BOLTS	STEEL, ASTM A307
15.	COWL WASHER	STEEL
16.	GUIDE BEARING	SELF LUBRICATING POLYMER

FIGURE NUMBER	FLANGE CLASS	SIZE	WORKING PRESSURE	HYDRO TEST PRESSURE
<b>930-DC</b>	ANSI B16.1 CLASS 125	10" & 12"	10-150 PSI (69-1034 kPa)	225 PSI (1551 kPa)
<b>930-UC</b>	ANSI B16.1 CLASS 250	10" & 12"	10-300 PSI (69-2068 kPa)	450 PSI (3102 kPa)

SIZE	10" (DN250)	12" (DN300)		
A	23.50" (570mm)	27.50" (699mm)		
B	33.00" (838mm)	39.88" (1013mm)		
WGT	475 lbs (216 kg)	625 lbs (284 kg)		

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

**GA INDUSTRIES, LLC**, a VAG Brand

DATE: 5-27-19      DRAWN BY: WJN

**10" & 12" KINETIC AIR & VACUUM VALVE**

**FIGURE 930**      DRAWING NO. **EAV-7050-W**      REV **A**